

Load Ranger • Model MSI-5300

STANDARD SPECIFICATIONS

Accuracy: 1.0% Approved to NTEP, Class III Standard

Capacity: 20,000 lbs. (10,000 kgs) per pad

Resolution: 20 lbs. (10 kgs), 50 lbs. (20 kgs) - NTEP

Power: 6 volt rechargeable (40 hours between charging)

Battery Charger:
115/230 VAC External, 12 VDC External

Display: 5 digit, 0.8 in. (20mm) LCD

Annunciators:
Low Battery

Operating Temperatures:
-25° to 140° F (-32° to 60° C)

Safe Overload:
150% of capacity

Ultimate Overload:
200% of capacity

Overall Weigh Pad Dimensions:
24.0 L x 15.5 W x 3.0 H in. (609 x 393 x 76 mm)

Weight: 43 lbs. (19 kgs) per pad



© 1998 by Measurement Systems International
Printed in U.S.A.
PUB.143-11-90B

"We Weigh Quality First"



Measurement Systems

INTERNATIONAL

14240 INTERURBAN AVENUE SOUTH

SEATTLE, WASHINGTON 98168-4660 U.S.A.

Ph: 206-433-0199 • Fax: 206-244-8470

Web: www.msiscales.com • Email: info@msiscales.com